

Cessna 172SP Checklist

For	Flight Si	mulator use only	
Before Start		After Take Off	
Parking Brake on		Taxi Lights Off	
Fuel On		Climb at 70 Kts	
Master Switch ON		Fuel Pump OFF	
Fuel Pump ON		-	
Mixture Rich		FREDA	
Beacon On		Fuel	
Check Clear		Radios	
Throttle 1/4"		Engine T's & P's	
Start engine		Direction Indicator (D)	
		Altimeter (B)	
After Start			
RPM 1000		Before Landing	
Γ's and P's		Brakes off	
vionics ON		Mixture Rich	
Direction Indicator (D)		Fuel Both Tanks	
Ntimeter (B)		Landing Light ON	
requencies set			
		After Landing	
Before Taxy		Landing Light OFF	
axi Lights ON		Taxi Light ON	
Parking Brake OFF		Nav lights OFF	
	-	Strobe light OFF	
Before Take Off	f	Squawk Standby	
Γrim set			
Vlixture Rich		Shut Down	
Magnetos Both		Parking brake ON	
Fuel Both Tanks		Taxi Light OFF	
Flaps up		Flaps Up	
Gauges check sensible		Avionics OFF	
Nav lights ON		Mixture Lean	
Strobe light ON		Fuel OFF	
Squawk Mode C		Beacon OFF	
Look Out		Master Switch OFF	